

### DUSTED FROST VINYL

Dusted Frost Vinyl is designed to provide protection against the scrutiny of prying eyes. Whilst completely opalescent, the film still allows most natural light to pass through.



Tintfit Window Films warranty

**VERTICAL 5 YEARS**  
**HORIZONTAL 3 YEARS**



Storage from -5°C to +40°C

**3 YEARS**



REACH RoHS compliant

**RESPECTED**

### TECHNICAL DATASHEET


Data calculated based on film applied to clear glass 3 mm thick (\*on double glazing 4-16-4)

Ultraviolet transmission	1 %
Visible light transmission	60 %
Reflection of external visible light	18 %
Reflection of internal visible light	18 %
Total solar energy rejected	28 %
Total solar energy rejected 2	29 %
Solar ratio :	
Solar energy reflection	18 %
Solar energy absorption	15 %
Solar energy transmission	67 %
Reduction in Solar Glare	40 %
g-value	0.71
u-value	5.6
Shading coefficient	NC
Installation type : External application	
Roll length	50 m
PET / PVC composition	PVC
Thickness	70 μ

Colour : SAND

### CONSTRUCTION

1. 75μ "cast" polymer PVC
2. Half Permanent Adhesive, allowing the "degassing" of the actual surface, and limits the adhesive transfer during removal
3. Paper release liner allowing digital cutting



### MAINTENANCE INSTRUCTIONS

Soapy water solution, do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

*Non-contractual data, Tintfit Window Films reserves the right to modify the composition of its films at any time.*

### INSTALLATION ADVICE

Vertical installation and on standard glass surface\*

Clear single pane	✓
Tinted single pane	✓
Reflective tinted single pane	✓
Clear double pane	✓
Tinted double pane	✓
Reflective tinted double pane	✓
Gas-filled double pane - Low E	✓
STADIP EXT. clear double pane	✓
STADIP INT. clear double pane	✓

✓ Yes ! Caution ✗ No

\*Recommendations provided on the basis of a glazed surface covering up to 2.5m<sup>2</sup>.