



## Certification

Rated A+ on VOC tests for indoor emissions.

Class BS EN 13501 fire resistance compliance rating, for permitted use in public spaces.



## Durability

This product offers exceptional resistance to water, dirt, abrasion, UV rays and wear (yellowing, crackling, scaling, delamination).



## Maintenance

A quick and easy material to maintain, its external surface's remarkable qualities facilitate cleaning, prevent marking and impede mould growth.

Maintenance can be performed with all types of household cleaning products, other than abrasive products such as acetone or white spirit.



Heat-shrinkable



Thickness

200  $\mu$  - 350  $\mu$



Elongation

Up to 220%



Fire-resistance rating BS EN 13501



UV resistant



Scratch resistant



### STRUCTURE

Calendered Vinyl Film with Polymeric Adhesive Coating.



### ADHESIVE STRENGTH

Dilation after 48 hours at 65c.  
Width: 0.9% - Length 0.6%  
Resistant to traction.  
Width: 262 kg / cm Length: 230 kg / cm



### PHYSICAL PROPERTIES

Tear resistance:  
Length: 5.1kgf / cm -  
Length: 6.9kgf / cm

Excellent resistance to abrasion, acid (ethanol, salt), stains, dirt, mold ... except Xylene.



### 10 YEARS WARRANTY

**ADHESIVE:**  
Acrylic and activated, moisture insensitive. This film is applied on clean, smooth, rigid and non-porous surfaces (glass, metal, plastics, wood ...)